


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
05/05/17	D	ADDED DIM. Ø3.10	T.B.	B.S.	
05/12/17	E	Dim. 57.50 was 57.40	T.B.	B.S.	
03/06/19	F	Updated to "ROHS Compliant"	T.B.	B.S.	

NOTES:

1. MATERIAL:

HOUSING : POLYPROPYLENE
 FLAMMABILITY RATING: UL94 HB, UL FILE NO. E216959
 TEMPERATURE RANGE: -10°C TO +100°C
 RIVETS: BRASS, NICKEL PLATED.
 SPRING: SPRING STEEL, NICKEL PLATED.
 9V SNAPS: BRASS, NICKEL PLATED
 CONTACT RESISTANCE: UNDER 50m Ω FOR ± CONTACTS PER
 EIA-540J000
 ROHS COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735	Scale	Drawn By B.S.
		Approved By T.B.	
decimal ±.5 (.020)	Title THREE "AA" CELL HOLDER WITH SNAP FASTENERS		
Fractional ± .8 (.030)	Date 03/06/19	Drawing Number BC3AASF	
Angular ± 3°			